


Architectural Acoustic Foam

Urethane Foam: Charcoal, Blue, Brown, Beige, Hunter Green & Burgundy
Melamine & Fireflex: Natural White



Anechoic Wedge											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TFW-2000	24" X 48"	2"	2lb./cubic foot		.15	.31	.73	1.04	1.08	1.12	.80
TFW-3000	" "	3"	" "		.24	.46	1.08	1.05	.98	.90	.90
TFW-4000	" "	4"	" "		.32	.93	1.43	1.33	1.29	1.21	1.25




Whisper Wedge Absorption Panel											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
WW-2000	24" X 48"	2"	2lb./cubic foot		.15	.31	.73	1.04	1.08	1.12	.80
WW-3000	" "	3"	" "		.24	.46	1.08	1.05	.98	.90	.90
WW-4000	" "	4"	" "		.32	.93	1.43	1.33	1.29	1.21	1.25



Pyramid Absorbtion Panel											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TFP-2	24" X 24"	2"	2lb./cubic foot		.14	.32	.72	1.01	1.05	1.08	.80
TFP-3	" "	3"	" "		.44	.48	1.19	1.12	1.16	1.16	1.00
TFP-4	" "	4"	" "		.39	.60	1.21	1.14	1.16	1.13	1.05



Max Wedge											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TF-MAX-6	12" X 12"	6"	2lb./cubic foot		.27	1.05	1.34	1.28	1.26	1.17	1.25
TF-MAX-8	" "	8"	" "		.41	1.05	1.42	1.36	1.37	1.51	1.30



Hanging Baffle											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	AS/U
TFB-3	24" X 48"	3"	2lb./cubic foot		4.44	6.00	10.00	15.50	17.90	19.20	12.20
FLAMMABILITY: UL94HF-1											



Cornertec-Room Triangle Corner Bass Trap											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	AS/U
CRNTEC24	12" X 24"	12"	2lb./cubic foot		3.60	9.70	9.50	8.25	6.80	5.15	8.60
CRNTEC48	12" X 48"	12"	" "								
FLAMMABILITY: UL94HF-1											



Architectural Acoustic Foam






Urethane Foam: Charcoal, Blue, Brown, Beige, Hunter Green & Burgundy
Melamine & Fireflex: Natural White



CASCADE AUDIO ENGINEERING

Spiraltec-Room Corner Bass Trap 10" Cylinder											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	AS/U
SPRIALTEC	24"	10" cylinder	2lb./cubic foot		4.25	8.35	8.95	7.30	6.15	4.65	7.70
SPRIALTEC	48"	10" cylinder	2lb./cubic foot		4.25	8.35	8.95	7.30	6.15	4.65	7.70
FLAMMABILITY: UL94HF-1											



White Melamine Acoustical Foams											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TF-Ceiling	24" X 24"	1.5"	0.7lbs/cubic foot (foam)		.22	.44	.85	.95	.97	.95	.80
TF-C/Ptd	(Painted)	1.5"	FLAMMABILITY: CLASS 1	PATTERNS:							
TF-CeilingB	(w/Backer)	2"	FLAME SPREAD: 10								
TF-C/PtdB	(Painted w/Backer)	2"	SMOKE DENSITY: 50								



Fireflex Anechoic Wedge											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TFX-1.5	24" X 48"	1.5"	0.7lbs/cubic foot (foam)								
TFX-2	"	2"	FLAMMABILITY: CLASS 1		.03	.31	.81	1.02	1.01	.96	.80
TFX-3	"	3"	FLAME SPREAD: 10		.13	.74	1.26	1.18	1.12	1.03	1.10
TFX-4	"	4"	SMOKE DENSITY: 50		.33	1.12	1.32	1.39	1.19	1.12	1.26



Fabtec-Fabric Covered Melamine Panels -Six Stock Colors Available											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
FAB1-24	24" X 48"	1"	0.7lbs/cubic foot		.19	.32	.85	.88	.58	.50	.65
FAB2-24	"	2"	FLAMMABILITY: CLASS 1		.32	.75	1.20	1.10	.90	.63	.99
FAB3-24	"	3"	FLAME SPREAD: 10		.49	1.03	1.27	1.18	1.03	.72	1.13
SMOKE DENSITY: 50											



Fireflex Pyramid Design											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
TFPX-2	16" X 16"	2"	0.7lbs/cubic foot		.09	.28	.79	.94	1.00	1.04	.75
TFPX-3	"	3"	FLAMMABILITY: CLASS 1		.10	.48	.91	1.11	1.11	1.14	.90
TFPX-4	"	4"	FLAME SPREAD: 10		.16	.56	1.11	1.13	1.13	1.21	1.00
SMOKE DENSITY: 50											



Fireflex Hanging Baffle											
ITEM #	SIZE	THICKNESS	DENSITY	FREQUENCY(Hz)	125	250	500	1K	2K	4K	A S/U
TFB-F3	24" X 48"	3"	0.7lbs/cubic foot		4.17	6.50	10.00	15.60	17.90	19.50	12.80
FLAMMABILITY: CLASS 1											
FLAME SPREAD: 10											
SMOKE DENSITY: 50											



Bend, OR 97702
info@cascadeaudio.com
www.cascadeaudio.com
F: 541.389.5273
P: 541.389.6821

